



Minimum On is constant at 4 for all lengths.
 Adjust is constant at 100 for all lengths.
 Maximum On varies dependent on length as in table below:

Length	Maximum On	Minimum Light out (measured)	Minimum Light out (perceived)
1	14	0.14	3.7
2	20	0.47	6.9
3	24	0.32	5.7
4	24	0.29	5.4
5	25	0.41	6.4
6	27	0.32	5.7
7	30	0.25	5
8	34	0.21	4.5
9	34	0.28	5.3
10	37	0.26	5.1
11	40	0.19	4.4
12	45	0.14	3.7
		0.273333	5.15

8	9	10	11	12
290	212	230	365	147
263	196	211	334	135
240	179	191	300	125
201	150	158	250	106
157	116	122	191	82
112	82	86	136	58
73	54	56	88	38
40	30	32	49.5	21
19.6	14.8	15	23.8	10
7.5	6	6.3	8.9	3.8
1.4	1.2	1.5	2.1	1.1
0.6	0.6	0.6	0.7	0.2

100	100	100	100	100
91.25475	91.32653	90.52133	89.82036	92.59259
76.42586	76.53061	74.88152	74.8503	78.51852
59.69582	59.18367	57.81991	57.18563	60.74074
42.58555	41.83673	40.75829	40.71856	42.96296
27.75665	27.55102	26.54028	26.34731	28.14815
15.20913	15.30612	15.16588	14.82036	15.55556
7.452471	7.55102	7.109005	7.125749	7.407407
2.851711	3.061224	2.985782	2.664671	2.814815
0.532319	0.612245	0.7109	0.628743	0.814815

0.228137	0.306122	0.28436	0.209581	0.148148
95.23%	96.15%	95.78%	95.66%	95.83%
4.55%	5.32%	5.11%	4.38%	3.69%

4.78	5.53	5.33	4.58	3.85
7.30	7.82	8.43	7.93	9.03
16.89	17.50	17.28	16.32	16.78
27.30	27.48	26.66	26.69	27.22
39.00	39.12	38.94	38.50	39.44
52.68	52.49	51.52	51.33	53.05
65.26	64.68	63.84	63.81	65.55
77.26	76.93	76.04	75.62	77.94
87.42	87.48	86.53	86.52	88.61
95.53	95.56	95.14	94.77	96.23
100.00	100.00	100.00	100.00	100.00